




云智科技
YDEACHN.COM

Service Hotline: 400-666-9216



Distributor Specification

T-2.0

Version: V02 Date: 2017-07-31

Product Summary

T2.0 Distributor is YDEA-TECH company's independent research and development of the LED display Distributor Fast Gigabit switch, multi-channel signal input and output management, intelligent split video signal, the signal reallocate organization fully supports online fault diagnosis, so that the system is running more stable and reliable, suitable for building displays, lighting engineering and other fixed installations.


Product Feature

- 1 Ethernet port input, 1 Ethernet port ring out.
- 8 Ethernet ports output.
- Two-way backup.
- Cascade stitching.
- Long distance cable transmission.
- Screen check function.


Technical Specifications

Input	1 RJ45	Compatibility	Micro Series
Signal loop	1 RJ45	Online upgrade	Support
Output	8 RJ45	Temperature	-10°C-60°C
Multi-machine in parallel	Support	Humidity	5% -95%
Two-way backup	Support	Power	100-240VAC 50/60HZ
Special display	Single distributor、Single port position any offset	Power consumption	25W
Transmission mode	Top to Bottom、Bottom to Top、Left to Right、Right to Left	Size (L × W × H)	200 × 150 × 44 (mm)
Transmission distance	100m	Weight	<1kg


Board Dimensions



Chassis Interface Definition



Board Interface Definition



- | | | | | | |
|-------------------|-------------------|-------------------|-------------------------|--------------------|--------------------|
| 1 Power | 2 Indicator | 3 Signal input | 4 Signal cascade output | 5 Signal output 1 | 6 Signal output 2 |
| 7 Signal output 3 | 8 Signal output 4 | 9 Signal output 5 | 10 Signal output 6 | 11 Signal output 7 | 12 Signal output 8 |