


# Jade Screen Series

Create a more Valuable Urban Advertising Media




Very see-through, without any change of architectural appearance and transparency of glass wall, create the open view in large space indoors, and make advertising emerge into architecture and life.



## Key Features

### 82% Transparency

Very see-through, without any change of architectural appearance and transparency of glass wall, make ad emerge into building and life.



### Smart control

Smart control by mobile APP, wireless data transmission, screen+ data cloud + APP, WIFI connection.




### Wider advertising Scope | viewing angle 120°

YIPLD Jade Screen delivers awe-inspiring picture quality across the entire screen, even from wide viewing angles.



### Modularized | DIY design

Any size screen combination flexible, no steel structure, no complicated installation, easy and convenient.




### High brightness | 5500cd / m<sup>2</sup>

still visible clearly under strong light.



# Jade Screen Series

Create a more Valuable Urban Advertising Media



## Screen Size

1000 × 500, 500 × 500

## Application Scenarios

Glass wall, large indoor space

## Jade Screen Series

- Transparency: 82%
- Brightness : 5500cd/m<sup>2</sup>
- Depth: 21mm
- Viewing Angle: 120°



Modularized



120° Wide Viewing Angle



Simple Colorful




New Configuration

## Other Features

### Super(or ultra) transparent

More than 82% transparency, the highest transparency in led screen industry.



### High contrast ratio

High contrast ratio 1500:1, stunning color, dynamic image and eye-catching.




### Smart

Smart control by mobile APP, wireless data transmission, screen+data cloud+APP, WIFI connection.



### High refresh rate

High refresh rate: in the industry, the minimum pixel pitch (able to mass production) 3mm, 3840HZ refresh rate.



### Simple

No complicated installation, No steel structure, fast positioning and fast installation, convenient and quick maintenance.




### New Configuration

The shape innovation of static glass, new screen displaying, new advertising type.




## Dimensions (unit : mm)

1000 × 500 × 73 /  
7 Kg




500 × 500 × 73 /  
4.25 Kg




## Connectivity

- ① Live wire
- ② Neutral wire
- ③ Earth wire
- ④ LAN



## 2 Types of Installation



Hang

Floor stand



# Specifications

Size (mm)	1000X 500		500X 500	1000X 500		500X 500
Model	J3			J10		
	-R1000	-L1000	-L500	-R1000	-L500	
Pixel Pitch (mm)	3.9 x 7.8			10.4 x 10.4		
Pixel Density (dot/m <sup>2</sup> )	32768			9216		
Module Resolution (dot)	256 X 64		128 X 64	96 X 48	48 X 48	
LED Type	SMD 3 in 1			SMD 3 in 1		
Brightness (cd/m <sup>2</sup> )	5500			5000		
Transparency	82%			87%		
Viewing Angle	120			120		
Grey Level	14bits			14bits		
Scan Mode	1/4			1/2		
Refresh Rate (Hz)	3840			3840		
Frame Frequency (Hz)	60			60		
Avg.Power Consumption(W/ m <sup>2</sup> )	240			300		
Max.Power Consumption(W/ m <sup>2</sup> )	800			800		
Maintenance	Back			Back		
IP	IP42			IP42		
Working Temp	-20~50°C			-20~50°C		
Weight (kg/ m <sup>2</sup> )	14		17	13		16

# System topology

